# **3M 54 Tape** Polyester Film Tape With Thermosetting Rubber Adhesive

Data Sheet

## **Product Description**

3M<sup>™</sup> 54 Tape is a 1-mil transparent polyester film with rubber thermosetting adhesive.

- 1-mil transparent polyester film backing
- Thermosetting rubber adhesive
- Supplied on 3 inch cores

Like all 3M insulating tapes, 3M 54 Tape is available in standard and custom widths and lengths. Standard length is 72 yards.

- Widths from 1/4" to 22.5"
- Longer lengths up to several times normal length, dependent upon width. Check with Customer Service.

## Applications

3M 54 Tape is especially suited for use is wrapping fine wire coils where magnet wire serves to color code.

Properties	Typical Values	
Adhesive	Thermosetting Rubber	
Backing	Polyester Film	
Backing Thickness <sup>1</sup>	1.0 Mil	
Total Thickness	2.5 mils/.063mm	
Color	Transparent	
Temperature Class	130°C /266°F	
Dielectric Breakdown <sup>1</sup>	5,500 Volts	
Insulation Resistance <sup>1</sup> (megohms)	>1 x 10 <sup>6</sup>	
Breaking Strength <sup>1</sup>	25 lbs./in. (44 n/10mm)	
Elongation <sup>1</sup> (% at break)	100	
Electrolytic Corrosion Factor <sup>2</sup>	1.0	
Adhesion to Steel <sup>1</sup>	45 oz./in. (4,9 n/10mm)	

\*Footnote: 1. Test method ASTM D 1000

2. 3M Test Method-Available on request

3M is a trademark of 3M.

#### **Important Notice**

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties,



#### **Electrical Products Division**

6801 River Place Blvd. Austin, TX 78726-9000 800 676 8381 http://www.3m.com/elpd expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS THAT WERE DEFECTIVE.

> © 3M 1998 78-8124-4755-1(A)